



Standard Direct Drive Aluminum Elevator

Industrial Duty Integrated with a New Ultra Modern Appeal

- All Aluminum and Stainless Steel Construction
- Low Draft Design
- Very Modern Compact Drive Units
- Stainless Steel Equalizer Arms with Quad Upper Rollers
- Stainless Steel Cables
- Adjustable Heavy Duty Guide Poles
- Piling or Seawall Mount
- Standard Angle is 25° (Available in Various Angles including Vertical)
- 15 Year Limited Warranty

Options:

- SEArmor Corrosion Resistant Winders for Long Lasting Durability
- Wash Down Stainless “Hurricane” Motors
- Wireless Remote Control
- Auto Stop and Limit Switch
- Complete Disconnect Switch
- Stainless Steel Wash Down “Hurricane” Motors
- Underwater Bracing (for Deepwater Applications)
- Cable Retention System



***See our “Complete list of Other Accessories”

⚡ Specifications ⚡

Size	Horse Power	Volt and Amperage	Cable Size and Length	Vertical Travel	Track Size	Max. Beam	Cradle Dimensions	Bunks	Pile Size
5,000 lb.	(2) 3/4 HP	120V/30A 240V/20A	5/16" x 30' Stainless Steel	12'	6" x 4" x 25' I-Beam	8' 0"	7' Dual Forks	3" x 8" x 12' Aluminum Bunks	8" Min.
7,000 lb.	(2) 3/4 HP	120V/30A 240V/20A	5/16" x 30' Stainless Steel	12'	8" x 5" x 25' I-Beam	8' 0"	7' Dual Forks	3" x 8" x 12' Aluminum Bunks	8" Min.
10,000 lb.	(2) 1 HP	120V/30A 240V/20A	5/16" x 30' Stainless Steel	12'	8" x 5" x 25' I-Beam	9' 0"	8' Dual Forks	3" x 10" x 12' Aluminum Bunks	10" Min.
12,000 lb.	(2) 3/4 HP	120V/30A 240V/20A	5/16" x 42' Stainless Steel	11'	10" x 6" x 25' I-Beam	10' 0"	8' Dual Forks	3" x 10" x 12' Aluminum Bunks	10" Min.
14,000 lb.	(2) 1 HP	120V/30A 240V/20A	5/16" x 42' Stainless Steel	11'	10" x 6" x 25' I-Beam	10' 0"	8' Dual Forks	3" x 10" x 14' Aluminum Bunks	10" Min.
15,000 lb.	(2) 1 HP	120V/30A 240V/20A	5/16" x 42' Stainless Steel	11'	10" x 6" x 25' I-Beam	10' 0"	8' Dual Forks	3" x 10" x 14' Aluminum Bunks	10" Min.
17,000 lb.	(2) 1 HP	240V/20A	5/16" x 56' Stainless Steel	11'	12" x 7" x 25' I-Beam	10' 0"	10' Dual Forks	3" x 10" x 14' Aluminum Bunks	12" Min.
20,000 lb.	(2) 1 HP	240V/20A	5/16" x 56' Stainless Steel	11'	12" x 7" x 25' I-Beam	12' 6"	10' Dual Forks	3" x 10" x 14' Aluminum Bunks	12" Min.